



**Canister**



**Table Top  
BHL D 60TT**

# Liquid Dispenser



**Floor Stand  
BHL D 60FS**



- Ideal for dispensing water based chemicals , Essence , Perfumes , Liquid medicines etc.
- Floor stand model BHL D-60FS has container holding capacity up to 40 Kg.
- Table top model BHL D-40TT has container holding capacity up to 10 Kg.
- Piston technology with high grade stainless steel tube & high grade Teflon washer which ensures smooth operation and long life.
- Accurate dispensing from 0.1 ml to 60 ml and 1/384 Ounce to 2 Ounce.
- Automatic stirring of liquids with a motorized stirring system , stirring time adjustable with a built in timer.( Default adjustment of 5 minutes per hour)
- Competitively priced and quick deliveries.
- Basic consumables and spares free with every machine.
- 15 - month warranty against any manufacturing defects.

# Liquid Dispenser Details

Sr. No.	Dispenser features	Floor Stand BHL D - 60 FS	Table Top BHL D - 60 TT
---------	--------------------	------------------------------	----------------------------

## CANISTER FEATURES

1	Dispensing Flow	Sequential	Sequential
2	Dispensing displacement	External	External
3	No of canister	16	16
4	Canister Size	112 OD x 255 Len. x 109 ID	112 OD x 255 Len. x 109 ID
5	Canister Volume	2 Liters	2 Liters
6	Canister Material	Poly-Propylene	Poly-Propylene
7	Canister Stirring	24 hrs Adjustable (Default set 5 min/hr)	24 hrs Adjustable (Default set 5 min/hr)
8	Minimum dispensing quantity	0.1 ml / OR 1/384 Ounce	0.1 ml / OR 1/384 Ounce
9	Maximum dispensing quantity	60 ml OR 2 Ounce	60 ml OR 2 Ounce

## CONTAINER HANDLING FEATURES

10	Minimum container height (mm)	65 mm	65 mm
11	Maximum container height (mm)	380 mm	270 mm
12	Maximum container dia. (mm)	300 mm	300 mm

## POWER SUPPLY / MACHINE ENVIRONMENT

13	Power Supply ( V )	230 VAC	230 VAC
14	Frequence ( Hz )	50 Hz	50 Hz
15	Max. Power absorption (w)	35 Watts	35 Watts
16	Working Temperature (Celsius)	5° to 45°	5° to 45°
17	Relative humidity	15% to 90%	15% to 90%
18	Gearbox Output RPM	25	25
19	Timer	24 hrs adjustable	24 hrs adjustable

## DISPENSER DIMENSIONS

20	Length (mm)	820 mm	820 mm
21	Depth (mm)	310 mm	310 mm
22	Height (mm)	1430 mm	720 mm
23	Machine Weight (Kg)	75 Kg	60 Kg
24	Machine + packaging weight (kg)	90 Kg	70 Kg
25	Floor Area	1m <sup>2</sup>	1m <sup>2</sup>

### Office Address

## Bholanath Precision Engineering Pvt.Ltd.

11,Kembros Industrial Estate,Near Asian Paint Company,  
Sonapur Lane,Bhandup (West),Mumbai - 400078,India.

### FACTORY ADDRESS

Plot No - 1, Gut No - 203 , Dahagaon , Vasind (West) , Wada Link Road ,  
Off Mumbai Nashik Road ,  
Opposite Jindal Steel Factory ,  
Taluka - Shahpur , District - Thane - 421 302 ,  
Maharashtra State , India.

### Contact Us

Phone No :-

+91 - 9821671733

+91 - 9920903825

+91 - 9930514603

+91 - 9323166582

91 - 22 - 25664338 /25662856 / 67993260



Website :-

www.bholanath.in

Email Id :-

support@bholanath.in  
nisha.k@bholanath.in